Multi-Door Networking Controller Panel

AR-716E

- Lockable housing prevents the violence.
- 2 RS-485 serial ports, each port supports 8 readers.
- 2 Wiegand ports for WG readers.
- 4 DI + 4 RO for various applications.
- Changeable interface, RS-485 or Ethernet.
- Extension relay board with 8 DI + 8 RO.
- Built-in power and RS-485 transmission LED indicators.
- Open-all-doors function for emergency purpose.
- Multi-door anti-pass-back function.
- Support time zone, door group and holiday editing.
- Data retained up to 60 days when the power failure.



Specifications

User Capacity		15,000
Event Log		11,000
Voltage		15-24 VDC
Power Consumption		< 2.5W
Communication Interface		Reader Channel : RS-485*2 Host Channel : RS-485 / Ethernet
Baud Rate	RS-485	9600 bps (N, 8, 1)
	Ethernet	10/100 Base T
Operating Temperature		-20°C to +75°C
Digital Input		4+8 (AR-716E-IO)
Relay Output		4+8 (AR-716E-IO)
Max. RS-485 Reader Supported		16
Max. WG Reader Supported		2
Anti-pass Back		Yes
Door Group		255
Time Zone		63
Editing Interface		PC Software
Dimension (mm)		180(L)x231(W)x62(H)
N.W. (g)		1,840 ± 50
Housing Material		Metal
Others		UPS Function (Battery not included)

Options

Extension Relay Board

AR-716E-IO

- Extension Relay Board for AR-716E Networking Controller
- 8 Sets of Exit Button Input with Photo Isolation
- 8 Sets of Door Relays (Form C)
- Door Relay Release Time setting via SOYAL Software

Serial Device Network Module

AR-727I V2

- Built-in Ethernet and TTL serial interface
- TCP/UDP Client / Server , DHCPc , IGMP and ARP supported

Specifications

Converting Interface	10/100 Base T Ethernet – UART (TTL)
Baud Rate	4800-115200 bps
Voltage	5 VDC
Operation Temperature	-20°C to +75°C
Protocol	TCP/UDP Client / Server , DHCPc , IGMP ARP
Dimension (mm)	46(L)x28(W)x15(H)
N.W. (g)	15± 5
AUTO MDI/MDIX	Yes

125kHz / 13.56MHz Reader

Specifications

Item Number	AR-737H/U	AR-721U	AR-721K	AR-661U
Product Series				
Frequency	125kHz / 13.56MHz	125kHz / 13.56MHz	125kHz / 13.56MHz	125kHz
Voltage	9-16 VDC / 9-24 VDC	9-16 VDC	9-16 VDC	12-18 VDC
Power Consumption	<1.5W / 70 mA	80 mA / <1W	350 mA	
Communication Interface	RS-485 (737H only), TTL Wiegand (737U only) and ABA-II	WG 26 / 34, ABA-II, ASYNC	WG 26 / 34, ABA-II, ASYNC	WG 26 / 34, ABA-II, ASYNC
Baud Rate	9600 bps / 19200 bps(N, 8, 1)	9600 bps (N, 8, 1)	9600 bps (N, 8, 1)	9600 bps (N, 8, 1)
Operating Temperature	-20°C to +75°C	-20°C to +75°C	-20°C to +75°C	-20°C to +75°C
Compliance (optional)	– • ISO14443A • ISO15693 • ISO14443A/B+15693	–	–	–
Reading Range	10-20 cm	3-8 cm	10-18 cm	3-8 cm	10-18 cm	3-8 cm	33-60 cm
Read / Write	Read Only	Read / Write	–	–	–
Supported Tags	EM4001 / EM4012	• MIFARE Ultra Light (L10) • MIFARE Standard (S50) • MIFARE Plus (P60)	–	–	–
Keypad	No	No	Yes	Yes
Indicator	1 bi-color LED and 1 beeper	1 bi-color LED and 1 beeper	1 bi-color LED and 1 beeper	3 LED and 1 beeper
Waterproof	Yes (Optional)	Yes (Optional)	No	Yes (Optional)
Color	Gray	Gray / Silver	Gray / Silver	Gray
Dimension (mm)	113(L)x71(W)x36(H)	81(L)x43(W)x18(H)	111(L)x77(W)x29(H)	228(L)x228(W)x38(H)
N.W. (g)	80 ± 10	40 ± 5	90 ± 10	1,000 ± 50
Housing Material	ABS	ABS	ABS	ABS

Networking Controller • Reader

MIFARE Door Lock/Master card

AR-323D

- Built-in Calendar
- Available for Stand-Alone and Networking System Built-in
- SOR MIFARE Advantages
- Door Alarm Prompt (Unclosed and Forced-Open)
- Capability to Unlock by Mechanical Key

Door Transfer Hinge

AR-321DH4

- 32AWG, 4-pair 12VDC / 320mA,45°X4.5 or 4.5"x4"

Specifications

Lock Body Type	US Type / EU Type
Door Thickness	35mm~45mm / 25mm~35mm
Door Hands	RH/RHRL/LH/LHR (Optional) / RHL/H(Optional)
Weight	3.0kg / 3.6kg
Material	Metal
Operating Environment	-20℃ ~ +50℃
Operating Humidity	15% ~ 95%RH
Unlock	Smart Card, Mechanical Key
Frequency	MIFARE 13.56MHz (ISO14443A)
Reading Range	0~2cm
Respond Time	<1.5 sec
Low Battery Voltage Warning	Yes (<5.3VDC)
Low Battery Voltage Solution	Capability to connect an external 9VDC power supply
Indicators	One bi-color LED One buzzer Conditions : 1.Green LED + 1 beep : operation ok 2.Green LED + 7 beeps after card presented : inside latch is locked up 3. Red LED + 2 beeps : operation error 4. 5 beeps after card presented : low battery warning
System	Stand-Along / Networking
Supply Voltage	6VDC (LRS-AAx 4, 2500mAH) / 12VDC (Supplied via AR-321DAX1)
Power Consumption	<40uA (Idle state) / <50mA
Lifetime of Battery	Approx. 8 months (6 times operation per day) / -
Accessory	Master Card x 2 Battery LR6-AA x 4 / Networking module x 1

Specifications

Door Bell PB AR-PB-321

Service Panel AR-PB-323

Input	V+		12VDC/100mA
	-V-		0V
	Private LED		Low Active / 20mA max.
	Cleanup LED		Low Active / 20mA max.
Output	Bell Relay		Form A Clean Contact 24VDC/2A
Input	V+		12VDC
	V-		0V
	Private Button		Internal Piezo Button
	Cleanup Button		Internal Piezo Button
Output	Private	LED Driver	Open Collect 12VDC/50mA max.
		Relay	Form A Clean Contact 24VDC/2A
	Cleanup	LED Driver	Open Collect 12VDC/50mA max.
		Relay	Form A Clean Contact 24VDC/2A

Advantages of SOR

1. Data Protection for Key A/B
2. 6-layer Managing Structures
3. User ID Assignable
4. Expiration Setup
5. Off-line Operation Available
6. Global Access Control
7. Built-in Command within Cards

Smart Card Reader & Holder

- Apply to various automation devices such as air conditioner, TV, door lock and other power supply equipment.
- Allows applying to stored-value system.
- Support both networking and Stand-Alone operation mode.
- Support SOYAL Open System Rules (SOR)

Specifications

Frequency	13.56MHz
User Capacity	1024 / Unlimited (SOR only)
Voltage	12-24 VDC (USB powered)
Power Consumption	<1W
Communication Interface	RS-485
Operation Temperature	-20°C to +75°C (0-90% non-condensing)
Compliance	• ISO14443A • ISO15693 • ISO14443A/B+15693
LED	White LED x2 (Status) Green LED (OK) Red LED (Error)
I / O	4 DI & 1 Relay Form C 3 Transistor outputs (open collector)
Color	Silver / White
Dimension (mm)	90(L)x86(W)x15(H)
N.W. (g)	100 ± 10
Housing Material	ABS

Programmer

The AR-737P is a programmer for MIFARE Smart Card System, designed to improve read / write performance of MIFARE applications. It can be applied in various fields such as access control and stored-value systems.Choosing the AR-737P is believed to create more opportunities for your business.

Specifications

Frequency		13.56MHz
Voltage		5 VDC (USB powered)
Power Consumption		<1.5W
Communication Interface	RS-232	Product PIN AR-737PDX2N21 Socket PIN AR-737PDX8N21
	USB	
Baud Rate	RS-232	9600 bps (N, 8, 1)
	USB	USB 2.0
Operating Temperature		-20°C to +75°C (0-90% non-condensing)
Compliance (optional)		• ISO14443A • ISO15693 • ISO14443A/B+15693
Supported Tags		MIFARE 1 (4Byte) MIFARE 1 (C50) MIFARE Ultra Light (L10) MIFARE Pro (C70)
Indicators		1 bi-color LED and 1 beeper
Color		Gray
Dimension (mm)		113(L)x71(W)x36(H)
N.W. (g)		150 ± 10
Housing Material		ABS
Others		SOR Supported

Converter

Serial Device Network Server

AR-727CM

- Built-in RS-232, RS-485 & Ethernet interface (AR-727I module)
- Built-in power and data transmission LED indicator for signal state

Specifications

Converting Interface	10/100 Base T Ethernet , RS-232 , RS-485
Baud Rate	4800 bps-115200 bps
Voltage	9-24 VDC
Power Consumption	<2W
OperatingTemperature	-20°C to +75°C
Protocol	TCP/UDP Client / Server, DHCPc , IGMP, ARP
Dimension (mm)	110(L)x62(W)x24(H)
N.W. (g)	240 ± 10
Housing Material	Metal

Isolated RS-232/RS-485 Converter

AR-701CM

- Automatic data direction control
- RS-232 powered from DTR, RTS (activation needed)
- Up to 32 units in RS-485 multi-door operation
- Built-in power and data transmission
- LED indicator for signal state

Specifications

Converting Interface	RS-232 – RS-485
Voltage	9-16 VDC
Power Consumption	<1.5 W
Operating Temperature	-20°C to +75°C
Effective Range	2M (RS-232) / 300M (RS-485)
Surge Protection	1KV ESD
Optional Isolation	2KV
Dimension (mm)	64(L)x55(W)x16(H)
N.W. (g)	40 ± 5

USB to RS-485 Converter

AR-321CM



Specifications

Item Number	AR-321CM
Converting Interface	USB – RS-485
Voltage	5 VDC
Current	Max. 200mA
Operating Temperature	-20°C to +75°C
Dimension (mm)	79(L)x37(W)x16.4(H)
N.W. (g)	50
Surge Protection	2KV
Electrical Isolation	2500VRMS
Baud Rate	2400~57600

TTL to RS-485 Signal Converter

AR-321L485

Specifications

Converting Interface	TTL – RS-485
Voltage	9-15 VDC
Current	Max. 100mA
Operating Temperature	-20°C to +75°C
Effective Range	300M
Dimension (mm)	52(L)x14(W)x11(H)
N.W. (g)	14

SOR MIFARE • Converter

Programmable Controller

AR-401E	2-Scan Channel Processor Module
AR-401DI16	16-Channel Digital Input Module
AR-401RO16	16-Channel Relay Output Module

Distributed Control I/O Systems

The AR-401E is a programmable controller that provides an optimum solution for access and industrial integrating in centralized and distributed system architectures. The AR-401 offers I/O event control and user friendly programming development tools fulfills PLC requirements in access system.

Specifications

Item Number	AR-401E	AR-401DI16	AR-401RO16
Event Log	10,000	–	
Voltage	9-24 VDC		
Power Consumption	<1W		
Communication Interface	RS-485 / Ethernet (optional)		
Baud Rate RS-485	9600 bps / 19200 bps(N, 8, 1)	4800 bps / 9600 bps / 19200 bps(N, 8, 1)	
Baud Rate Ethernet	10/100 Base T		
Channel	2 RS-485 Scan Channels 1 RS-485 for Host (replaceable to Ethernet Module)	16 N.C. Contact Input Loop Condition Open/Close/Break	16 Form C Relay Output
LED Indicator	Power, Tx / Rx	Power, TX/RX(Input: Close/ Open/ Break, Network: Link/ACT/Busy	Power, Tx / Rx, Relay On / Off
Data Capacity	8M Bytes SDRAM Memory 80 Days Memory Backup	–	–
Remote IO Capacity	512 I/O	–	–
Virtual IO Capacity	512	–	–
Sequential Step	2048	–	–
Real Time Clock	Yes	–	–
Dimension (mm)	97(L)x44(W)x180(H)		
N.W. (g)	600 ± 50		
Housing Material	Metal		

Power Supplier

Specifications

Item Number	Input Voltage	Output Voltage	Dimension (mm)
BP-W12-1000-EO (EO)	100-240 VAC, 50 / 60 Hz, 0.3A	12 VDC, 1000 mA	65(L)x51(W)x66(H)
BP-W12-1000-US2 (US)	100-240 VAC, 50 / 60 Hz, 0.3A	12 VDC, 1000 mA	77(L)x45(W)x26.5(H)
BP-W15-2400 (Optional)	100-240 VAC, 50 / 60 Hz, 0.7A	15 VDC, 2400 mA, 36VA	97(L)x46(W)x34(H)

Proximity Card / Tag

Specifications

Card / Key Chain		Standard Card (Thick)	ISO Card (Thin)	125kHz Key Chain		MIFARE Card	MIFARE Key Chain	13.56MHz
Item No	Read	AR-TAGC1R50	AR-TAGC1R50	AR-TAGK1IR20	–	AR-TAGK61R20	–	–
	Read/Write	AR-TAGC1W50	AR-TAGC1W50	–	AR-TAGK31W20	AR-TAGK61W20	AR-TAGC3W50	AR-TAGK33W20	AR-TAGK63W20
Dimension (mm)		54(L)x86(W)x1.8(D)	54(L)x86(W)x0.8(D)	37(L)x30(W)x7.5(D)	39(L)x35(W)x6.5(H)	45(L)x26(W)x5.2(H)	54(L)x86(W)x0.8(D)	39(L)x35(W)x5.5(H)	45(L)x26(W)x5.2(H)
Data Format		EM4001 / 4012 SOYAL Format				MF1			
Frequency		125 kHz				13.56 MHz			
Transponder Type		Passive (non-battery operated)							
Operating Temperature		-30°C to +75°C							

Product Selection and Part Number (How to Order)

AR-TAG X X X X X X

Model No. / Others / Color / Read / RW / Frequency

Model	C Card	T Thick I ISO P Paper
	T Tag	1 12mm 2 16mm 3 20mm 4 25mm 5 30mm
	K Key Chain	1 Shank 1 (small) 2 Sharp2 3 Sharp3 (Large)
Frequency	1	3 13.56MHz(MF1)+Stored-Value 5 13.56MHz(4K) 7 14443A/B+15693
	2 13.56MHz(Ultra Light)	4 13.56MHz(S1) 6 14443A/B
Read/RW	R Read Only W Read + Write	
Color	1 Silver 2 Gray 3 Blue 4 Black 5 Ivory 6 OEM	

Fingerprint Device

Specifications

Item Number	AR-821F (DO/MT)
Product Series	9000 DO 9000 MT
Frequency	125kHz / 13.56MHz
User Capacity	10,000
Event Log	11,000
Voltage	9-24 VDC
Power Consumption	<5W
Communication Interface	RS-485 / Ethernet (optional)
Baud Rate RS-485	9600 bps (N, 8, 1)
Baud Rate Ethernet	10/100 Base T
Operating Temperature	-20°C to +75°C
Compliance (optional)	– • ISO14443A • ISO15693 • ISO14443A/B + 15693
Door Relay Time	0 , 0.1 - 600 sec.
Alarm Relay Time	0 , 1 - 600 sec.
Aux. WG Port	WG 26/34, ABA-II
Lift Control	32 stops / 5000 users
Door Group	255
Time Zone	63
Editing Interface	Controller / PC Software
Reading Range	8-15 cm / 3-8 cm
Color	Gray
Real Time Clock	Yes
Housing Material	ABS
LCD Panel (pixel)	128*64 (4 line messages, 16 characters each line)
Dimension (mm)	132(L)x144(W)x102(H)
N.W. (g)	460 ± 10
Access Mode Check FP	Fingerprint Only
Access Mode No Check FP	Card only / Card + FP / PIN + FP / Card + PIN + FP
Fingerprint Sensor	Optical Sensor (9000 DO) / Capacitive Sensor (9000 MT)
Fingerprint Modual's CPU	400 MHz DSP
FER	< 0.1%
Enrollment time	800 msec / 500 msec
1:1 Verification time	800 msec / 500 msec
1:1000 Identification time	970 msec / 650 msec
Image size	384 Bytes
Fingerprint capacity	2250~4500(Depends on enrolled 1 or2 FP per user)
Encryption	256 bit AES (fingerprint data protection)
Size (mm)	63(L) x 43(W) x 10(H)

Relay Output Module

Specifications

Item Number	AR-821RB	AR-829RB
Voltage	12 VDC	
Operating Temperature	-20°C to +60°C	
Current	20 mA	40 mA
Output Contact	1 Form C, 10A at 120VAC, 10A at 24VDC	2 Form C, 2A at 120VAC, 2A at 24VDC
Dimension (mm)	20(L)x32(W)x29(H)	55(L)x26(W)x17.4(H)

Peripheral • Fingerprint Device • Programmable Controller • Proximity Card / Tag

Networking & Stand-alone Controller / Reader

Specifications

Item Number	AR-721H	AR-721H	AR-725H / AR-725H-M	AR-757H	AR-727H	AR-727H
Product Series			725H-M			
Frequency	125kHz / 13.56MHz	125kHz / 13.56MHz	125kHz / 13.56MHz	125kHz / 13.56MHz	125kHz	125kHz / 13.56MHz
Voltage	9-16 VDC / 9-24 VDC	9-16 VDC	10-24 VDC	9-16 VDC	10-24 VDC	10-24 VDC
Power Consumption	<3W	<3W	<3W	<3W	<3W	<3W
Communication Interface	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485
Baud Rate	9600 bps (N, 8, 1)	9600 bps (N, 8, 1)	9600 bps (N, 8, 1), 10/100 Base T	9600 bps (N, 8, 1)	9600 bps (N, 8, 1)	9600 bps (N, 8, 1)
Operating Temperature	-20°C to +75°C	-20°C to +75°C	-20°C to +75°C	-20°C to +75°C	-20°C to +75°C	-20°C to +75°C
Digital Input	Egress Button / Door Sensor	Egress Button / Door Sensor	2 Egress Button /2 Door Sensor	Egress Button / Door Sensor	Egress Button / Door Sensor / Arming Switch	Egress Button / Door Sensor / Arming Switch
Compliance (optional)	–	–	–	–	–	–
		• ISO14443A • ISO15693 • ISO14443A/B + 15693	• ISO14443A • ISO15693 • ISO14443A/B + 15693	• ISO14443A • ISO15693 • ISO14443A/B + 15693	• ISO14443A • ISO15693 • ISO14443A/B + 15693	• ISO14443A • ISO15693 • ISO14443A/B + 15693
Relay Output	Door Relay	Door Relay	Door Relay	Door Relay / Alarm Relay	Door Relay / Alarm Relay	Door Relay / Alarm Relay
Door Relay Time	0 , 0.1-600 sec.	0 , 0.1-600 sec.	0 , 0.1-600 sec.	0 , 0.1-600 sec.	0 , 0.1-600 sec.	0 , 0.1-600 sec.
Alarm Relay Time	0 , 1 - 600 sec.	0 , 1 - 600 sec.	0 , 1 - 600 sec.	0 , 1 - 600 sec.	0 , 1 - 600 sec.	0 , 1 - 600 sec.
Tamper Resist. Switch	Limit Switch (Form C)	Limit Switch (Form C)	Limit Switch (Form C)	Limit Switch (Form C)	Limit Switch (Form C)	Limit Switch (Form C)
User Capacity	M4 / M8	1,024 / 1,024	1,024 / 1,024	1,024 / 1,024	1,024 / 1,024	1,024 / 1,024
Event Log	M6 / M8	65,535 / 1,200	65,535 / 1,200	65,535 / 3,000	65,535 / 1,200	65,535 / 1,200
Aux. WG Port		WG 26/34, ABA-II	WG 26/34, ABA-II	WG 26/34, ABA-II	WG 26/34, ABA-II	WG 26/34, ABA-II
Anti-pass-back (M4 /M8)		1,024 / 1,024	1,024 / 1,024	3,000 / 1,024	1,024 / 1,024	1,024 / 1,024
Lift Control (M4 /M8)		32 stops, 1,024 users	32 stops, 1,024 users	32 stops, 1,024 users	32 stops, 1,024 users	32 stops, 1,024 users
Proximity Reading Range		3-5cm	10-18cm / 3-8cm	10-15cm (725H) / 7-14cm(729H)	10-18cm / 3-8cm (relay)	3-5cm (725H) / 2-5cm(729H)	10-18cm / 3-8cm	10-18cm / 3-8cm
Serial Out		TTL (4800 bps, N, 8, 1) (shared with alarm relay)	TTL (4800 bps, N, 8, 1) (shared with alarm relay)	TTL (4800 bps, N, 8, 1) (shared with alarm relay)	TTL (4800 bps, N, 8, 1) (shared with alarm relay)	TTL (4800 bps, N, 8, 1)	TTL (4800 bps, N, 8, 1)
Real Time Clock		Yes	Yes	Yes	Yes	Yes	Yes
LCD Panel (pixel)		–	–	–	–	128*64 (4 line messages, 16 characters each line)	128*64 (4 line messages, 16 characters each line)
Door Bell Button		No	No	Yes	Yes	No	No
Transistor Output		Duress/Alarm/Arming LED	Duress/Alarm/Arming LED	Duress/Alarm/Arming LED /2nd Door Open	Duress/Arming LED /Door Bell	Duress/Arming LED /Card Present	Duress/Arming LED /Card Present
Weatherproof		IP54	–	IP54	IP54	IP54	IP54
Dimension (mm)		114(L)x78(W)x28(H)	111(L)x77(W)x26(H)	125(L)x89(W)x30(H)	126(L)x91(W)x32(H)	140(L)x92(W)x33(H)	126(L)x91(W)x46(H)
Indicator		5 bi-color LED and 1 beeper	1 bi-color LED and 1 beeper	1 bi-color LED and 1 beeper	3 LED and 1 beeper	6 bi-color LED and 1 beeper	1 bi-color LED and 1 beeper
Keypad		Stainless Steel	Rubber	Touch Panel	Rubber	Stainless Steel	ABS
Housing Material		Zinc Alloy	ABS	Zinc Alloy + PC RESIN	ABS	Zinc Alloy	ABS
Color		Chrome	Gray / Silver	Black/Gray/Silver/Blue/Red/ Orange/White/Green/Yellow	Gray / Silver	Chrome	Gray
N.W. (g)		340± 10	100 ± 10	140 ± 10 (725H-M) 470± 10 (725H-M)	155 ± 10	430 ± 10	200 ± 10

Options

Access Mode

- M4 – – – Card only, Card+9-digit PIN, 9-digit PIN Only (9-digit PIN = 5-digit User Address + 4-digit Individual PIN)
- M6 – – – Card only, Card+4-digit Public PIN , 4-digit Public PIN Only
- M8 – – – Card only, Card + 4-digit Individual PIN , 4-digit PIN Individual Only

Specifications

Item Number	AR-829E	AR-725E / AR-725E-M
Product Series		725E-M
Frequency	125kHz / 13.56MHz	125kHz / 13.56MHz
Voltage	9-24 VDC	10-24 VDC
Power Consumption	<5W	<3W
Communication Interface	RS-485	Ethernet (AUTO MDI/MDIX) / RS-485
Baud Rate	9600 bps (N, 8, 1)	9600 bps (N, 8, 1), 10/100 Base T
Operating Temperature	-20°C to +75°C	-20°C to +75°C
Digital Input	Egress Button / Door Sensor / Arming Switch	2 Egress Button / 2 Door Sensor
Compliance (optional)	– • ISO14443A • ISO15693 • ISO14443A/B + 15693	– • ISO14443A • ISO15693 • ISO14443A/B + 15693
Relay Output	Door Relay Output / Alarm Relay Output	Door Relay
Door Relay Time	0 , 0.1 - 600 sec.	0 , 0.1-600 sec.
Alarm Relay Time	0 , 1 - 600 sec.	0 , 1 - 600 sec.
Tamper Resist. Switch	Limit Switch (Form C)	Limit Switch (Form C)
User Capacity	15,000	16,000 (M4/M8) / 65,535(M6)
Event Log	15,000	30,000
Aux. WG Port	WG 26/34, ABA-II	WG 26/34, ABA-II
Anti-pass-back	15,000	16,000
Lift Control	64 stops / 15000 users	32 stops, 16,000 users
Access mode	Card Only / Card or PIN / Card+PIN	Card Only / Card or PIN / Card+PIN

Item Number	AR-829E	AR-725E / AR-725E-M
Product Series		AR-725E
Proximity Reading Range	8-15cm / 3-8 cm	10-15cm (725E) / 5-9cm (725E-M) / 3-8cm (725E) / 3-5cm (725E-M)
Serial Out	TTL (4800 bps, N, 8, 1)	RS-485 / TTL (4800 bps, N, 8, 1) (shared with alarm relay)
Editing Interface	Controller / PC Software	
Door Group	255	
Time Zone	63	
Real Time Clock	Yes	
LCD Panel (pixel)	128*64 (4 line messages, 16 characters each line)	–
Transistor Output	Duress / Alarm / Arming LED	Card and Door Open
Weatherproof	No	IP54
Dimension (mm)	128(L)x96(W)x35(H)	125(L)x89(W)x30(H)
Indicator	6 bi-color LED and 1 beeper	1 bi-color LED and 1 beeper
Keypad	No	Rubber
Housing Material	ABS	Zinc Alloy + PC RESIN
Color	Gray / Silver	Black/Gray/Silver/Blue/Red/ Orange/White/Green/Yellow
N.W. (g)	230 ± 10	140 ± 10(725E) / 470± 10(725E-M)

Controller+Reader